



File No. <u>6426</u>

State law requires that the Bureau's copy be filed by the water well driller within 60 days after completion of the well.

1. WELLOWNER Name King Ranch	f) Duration of test: Pumping time 2 hrs. g) Recovery time • 5 () hrs. h) Recovery water level 1 / ft. at 1 hrs. after
2. CURRENT MAILING ADDRESS	h) Recovery water level 1 / ft. at 1 hrs. after pumping stopped.
P.O. Box 408 Frenchtown, Mt.59934	Wells intended to yield 100 gpm or more shall be tested for a period of 8 hours or more. The test shall follow the development of the well, and shall be
	conducted continuously at a constant discharge at least as great as the in- tended appropriation. In addition to the above information, water level data
3. WELL LOCATION 14 SE 14 NW 14 Section 34	shall be collected and recorded on the Department's "Aquifer Test Data" form.
Township 15n N/S Range 21w E/W County Msla	NOTE: All wells shall be equipped with an access port 1/2 inch minimum or
Govn't Lot, or Lot, Block	a pressure gauge that will indicate the shut-in pressure of a flowing well. Removable caps are acceptable as access ports.
Subdivision Name Tract Number	11. WAS WELL PLUGGED OR ABANDONED? Yes X No
4. PROPOSED USE: DomesticXIX Stock ☐ Irrigation ☐	If yes, how?
Other 🗆 specify	12. WELL LOG
5. TYPE OF WORK:	Depth (ft.) From To Formation
New well X⊠ Method: Dug □ Bored □	0 2 seil
Deepened □ Cable □ Driven Ŋ Reconditioned □ Rotary XIX Jetted □	2 29 sand, grave1 29 32 sand, grave1
	32 166 sand, clay Layers
6. DIMENSIONS: Diameter of Hole Dia in. from ft. toft.	166 184 sand, gravel
Diain. fromft. toft.	
Dia in. from ft. to ft.	
7. CONSTRUCTION DETAILS:	
Casing; Steel Dia_6" from_+2 ft. to_184 ft.	
Threaded □ Welded Ø Diafromft. toft. Type A 5 3 B Wall Thickness 2 5 0	
Casing; Plastic Diafromft. toft. Weight	
PERFORATIONS: Yes □ No ☒ Type of perforator used	
Type of perforator usedin. byin.	
ft. toft.	
perforations fromft. toftperforations fromft. toft.	
SCREENS: Yes □ No Ø	
Manufacturer's Name	
Type Model No	
Dia.	
GRAVEL PACKED: Yes NoVCK Size of gravel	
Gravel placed from ft. to ft.	
GROUTED: To what depth?ft. Material used in grouting entonite. Sealed as requ	1 100000
	tred by rule #30-21-554.
8. WELL HEAD COMPLETION:	ATTACH ADDITIONAL CULTURE AUTOTOCARY
Pitless Adapter ☐ Yes XINo	ATTACH ADDITIONAL SHEETS IF NECESSARY
9. PUMP (if installed) Manufacturer's name	13. YELLOWSTONE CLOSURE AREA: WATER TEMPERATURE
Type Model No HP	14. DATE COMPLETED 5-9-96
10. WELL TEST DATA	15. DRILLER/CONTRACTOR'S CERTIFICATION
The information requested in this section is required for all wells. All depth measurements shall be from the top of the well casing.	This well was drilled under my jurisdiction and this report is true to the best of
All wells under 100 gpm must be tested for a minimum of one hour and provide the following information:	my knowledge.
a) Air X Pumo Bailer	5-10-96 Date
b) Static water level immediately before testing 12 ft. If flowing; closed-in pressure psi. gpm.	Jerome's Drilling Co; Inc.
Flow controlled by:valve,reducers, other, (specify)	Firm Name
c) Depth at which pump is set for test	P O Box 4845, Missoula, MT 59806
d) The pumping rate: 100 gpm. e) Pumping water level ft. at hrs. after	Leven A Sucra 349
pumping began.	Signature License No.
MONTANA DEDA DEMENT OF NATURAL PROCUR	CEC & CONCEDVATION DAIDA
MONTANA DEPARTMENT OF NATURAL RESOURCE	

FILMED